



NOTE:
 INTERIOR VAPOR SEAL
 MAY BE REQUIRED IN COOLERS.
 PROJECT DESIGNER RESPONSIBLE
 FOR SPECIFYING REQUIREMENTS.

* NOTE:
 USE EXTERIOR RIDGE TRIM [F3371] FOR
 SLOPES UP TO 4 TO 12, FOR SLOPE
 GREATER THAN 4 TO 12 CONSULT
 FACTORY FOR PART NUMBERS.

* NOTE:
 USE INTERIOR RIDGE TRIM [F3504] FOR
 SLOPES UP TO 4 TO 12, FOR SLOPE
 GREATER THAN 4 TO 12 CONSULT FACTORY
 FOR PART NUMBERS.

REFER TO SHEET "CI-INFO" FOR ADDITIONAL INFORMATION REGARDING
 THE APPLICATION OF SEALANTS, FASTENERS, AND CLOSURE MATERIALS.
 CONSULT METL-SPAN TO DETERMINE ALLOWABLE LOAD AND SPACING
 OF ATTACHMENT FASTENERS.

ROOF THICKNESS TR	ROOF CLIP	ROOF CLIP SCREW TYPE III	ROOF CLIP SCREW TYPE V	ROOF CLIP SCREW TYPE B
3"	4103GNC	1616PNC	1724PNC	1816PNC
4"	4104GNC	1616PNC	1724PNC	1816PNC
5"	4105GNC	1616PNC	1724PNC	1816PNC
6"	4106GNC	1616PNC	1724PNC	1816PNC

ROOF PANEL WIDTH	RIDGE CLOSURE
CFR-42 (3'-6" WIDE)	7900GBK (BLACK)
CFR-42 (3'-6" WIDE)	7900GPW (POLAR WHITE)
CFR-42 (3'-6" WIDE)	7900GST (SAND STONE)
CFR-36 (3'-0" WIDE)	7902GBK (BLACK)
CFR-30 (2'-6" WIDE)	7901GBK (BLACK)

FREEZER OR COOLER

RIDGE DETAIL

2-CFR-14

DATE: April 4, 2017