



NOTE:
 INTERIOR VAPOR SEAL
 MAY BE REQUIRED IN COOLERS.
 PROJECT DESIGNER RESPONSIBLE
 FOR SPECIFYING REQUIREMENTS.

* NOTE:
 USE EXTERIOR RIDGE TRIM [F3371] FOR
 SLOPES UP TO 4 TO 12, FOR SLOPE
 GREATER THAN 4 TO 12 CONSULT
 FACTORY FOR PART NUMBERS.

* NOTE:
 USE INTERIOR RIDGE TRIM [F3504] FOR
 SLOPES UP TO 4 TO 12, FOR SLOPE
 GREATER THAN 4 TO 12 CONSULT FACTORY
 FOR PART NUMBERS.

REFER TO SHEET "CI-INFO" FOR ADDITIONAL INFORMATION REGARDING
 THE APPLICATION OF SEALANTS, FASTENERS, AND CLOSURE MATERIALS.
 CONSULT METL-SPAN TO DETERMINE ALLOWABLE LOAD AND SPACING
 OF ATTACHMENT FASTENERS.

ROOF THICKNESS TR	ROOF CLIP	ROOF CLIP SCREW TYPE III	ROOF CLIP SCREW TYPE V	ROOF CLIP SCREW TYPE B
3"	4224GNC	1616PNC	1724PNC	1816PNC
4"	4232GNC	1616PNC	1724PNC	1816PNC
5"	4240GNC	1616PNC	1724PNC	1816PNC
6"	4248GNC	1616PNC	1724PNC	1816PNC

ROOF PANEL WIDTH	RIDGE CLOSURE
CFR-42 (3'-6" WIDE)	7900GBK (BLACK)
CFR-42 (3'-6" WIDE)	7900GPW (POLAR WHITE)
CFR-42 (3'-6" WIDE)	7900GST (SAND STONE)
CFR-36 (3'-0" WIDE)	7902GBK (BLACK)
CFR-30 (2'-6" WIDE)	7901GBK (BLACK)

FREEZER OR COOLER	RIDGE DETAIL DIAPHRAGM CLIP OPTION	2-CFR-15
	© 2016 Metl-Scan, an NCI Building Systems company. All rights reserved.	DATE: Nov. 9, 2016