



PANEL CAP INSTALL IMMEDIATELY TO PROTECT AGAINST WEATHER, (BY OTHERS)

PARAPET CAP (BY OTHERS)

VAPOR BARRIER (BY OTHERS) SEAL TO FACE OF PANEL

METAL CLEAT (BY OTHERS)

LOW PROFILE SCREW 12" O.C. (BY OTHERS)

SEALANT TAPE [7405BWH]

FLUTE PLUG STRIP ONE PER PANEL [7607UGR] (IF REQUIRED)

FOAM IN PLACE INSULATION (BY OTHERS)

CLIP FASTENERS (ADDITIONAL FASTENERS WILL BE REQUIRED BASED ON NEGATIVE WIND PRESSURES)

4" x 3/4" - 14 GA. 4 HOLE CF CLIP [4633GNC] OR [4633SNC STAINLESS OPTION]

METL-SPAN INSULATED WALL PANEL

WARM SIDE

LOW PROFILE SCREW (BY OTHERS)

#14x7/8" SELF DRILL SCREW @ 8" O.C. [1007P]

SEALANT TAPE [7300BGR]

CANT (BY OTHERS)

ROOF, MEMBRANE WITH SEALANT & METHOD OF INSTALLATION BY OTHERS

ANGLE (BY OTHERS)

COLD SIDE

REFER TO SHEET "CS-INFO" FOR ADDITIONAL INFORMATION REGARDING THE APPLICATION OF SEALANTS, FASTENERS AND CLOSURE MATERIALS.

PARAPET DETAIL

APPLICATION:  
FREEZER OR COOLER

CS-PE-01