



- * NOTE:
USE EXTERIOR RIDGE TRIM [F3371] FOR SLOPES UP TO 4 TO 12, FOR SLOPE GREATER THAN 4 TO 12 CONSULT FACTORY FOR PART NUMBERS.
- * NOTE:
USE INTERIOR RIDGE TRIM [F3504] FOR SLOPES UP TO 4 TO 12, FOR SLOPE GREATER THAN 4 TO 12 CONSULT FACTORY FOR PART NUMBERS.

REFER TO SHEET "CI-INFO" FOR ADDITIONAL INFORMATION REGARDING THE APPLICATION OF SEALANTS, FASTENERS, AND CLOSURE MATERIALS. CONSULT METL-SPAN TO DETERMINE ALLOWABLE LOAD AND SPACING OF ATTACHMENT FASTENERS.

ROOF THICKNESS TR	ROOF CLIP	ROOF CLIP SCREW TEK III	ROOF CLIP SCREW TEK V	ROOF CLIP SCREW TYPE B
2"	4102GNC	1616PNC	1724PNC	1816PNC
2.5"	4125GNC	1616PNC	1724PNC	1816PNC
3"	4103GNC	1616PNC	1724PNC	1816PNC
4"	4104GNC	1616PNC	1724PNC	1816PNC
5"	4105GNC	1616PNC	1724PNC	1816PNC
6"	4106GNC	1616PNC	1724PNC	1816PNC

ROOF PANEL WIDTH	RIDGE CLOSURE
CFR-42 (3'-6" WIDE)	7900GBK (BLACK)
CFR-42 (3'-6" WIDE)	7900GPW (POLAR WHITE)
CFR-42 (3'-6" WIDE)	7900GST (SAND STONE)
CFR-36 (3'-0" WIDE)	7902GBK (BLACK)
CFR-30 (2'-6" WIDE)	7901GBK (BLACK)

COMMERCIAL AND INDUSTRIAL

CFR RIDGE DETAIL

CI-CFR-RG-01

DATE: Nov. 9, 2016