


7.2 Insul-Rib™ Wall Panels, 22 Ga. Exterior / 26 Ga. Interior Facings
Allowable Load^{1,3,4,5,6,11} (psf) Chart for Two or More Equal Spans

Panel Type ²	Span Condition	Design Criteria ^{7,8,9,10}	Support Span												
			4 ft	5 ft	6 ft	7 ft	8 ft	9 ft	10 ft	11 ft	12 ft	13 ft	14 ft	15 ft	
2.5" CF-7.2 Insul Rib	Two Spans	Bending and Shear	143.1	95.2	68.5	52.0	41.0	33.3	27.6	23.3	20.0	17.4	15.2	13.5	
		L/180	577.2	320.3	201.2	137.2	99.1	74.7	58.1	46.3	37.6	31.0	25.9	21.9	
		Pattern FP1	27.1	24.1	22.1	20.7	19.6	18.8	18.1	17.5	17.0	15.7	14.6	13.5	
		Pattern FP2	35.0	28.0	23.4										
		Pattern FP3	50.9	40.8	34.0	29.1	25.5	22.6	20.3	18.5					
	Pattern FP11	143.1	95.2	68.5	52.0	41.0	33.3	27.6	23.3	20.0	17.4	15.2	13.5		
	Three or More Spans	Bending and Shear	171.6	113.1	80.9	61.2	48.2	39.1	32.5	27.5	23.6	20.5	18.0	15.9	
		L/180	492.7	278.6	177.1	121.7	88.1	66.4	51.5	40.9	33.0	27.1	22.6	19.0	
		Pattern FP1	30.4	27.0	24.8	23.2	22.0	21.0	20.3	19.7	19.1	17.7	16.4	15.3	
		Pattern FP2	39.3	31.4	26.2										
Pattern FP3		57.1	45.7	38.1	32.6	28.5	25.4	22.8	20.7						
Pattern FP11	161.5	113.1	80.9	61.2	48.2	39.1	32.5	27.5	23.6	20.5	18.0	15.9			
3" CF-7.2 Insul Rib	Two Spans	Bending and Shear	147.5	99.4	72.4	55.6	44.3	36.3	30.3	25.8	22.3	19.5	17.1	15.2	
		L/180	601.4	339.6	217.2	150.9	111.0	85.1	67.2	54.4	44.9	37.5	31.8	27.2	
		Pattern FP1	42.4	35.8	31.3	28.1	25.6	23.7	22.2	20.9	19.9	18.3	17.0	15.2	
		Pattern FP2													
		Pattern FP3	57.4	46.1	38.4	33.0	28.8	25.6	23.0						
	Pattern FP11	144.6	99.4	72.4	55.6	44.3	36.3	30.3	25.8	22.3	19.5	17.1	15.2		
	Three or More Spans	Bending and Shear	175.5	116.8	84.4	64.4	51.2	41.9	35.0	29.8	25.8	22.6	19.9	17.7	
		L/180	521.0	300.9	195.5	137.0	101.3	77.7	61.4	49.5	40.7	33.8	28.5	24.3	
		Pattern FP1	47.4	39.9	34.9	31.3	28.6	26.4	24.8	23.4	22.2	20.5	19.0	17.7	
		Pattern FP2													
Pattern FP3		64.2	51.4	42.8	36.7	32.1	28.5	25.7							
Pattern FP11	161.8	116.8	84.4	64.4	51.2	41.9	35.0	29.8	25.8	22.6	19.9	17.7			
4" CF-7.2 Insul Rib	Two Spans	Bending and Shear	153.8	105.4	78.2	61.0	49.3	41.0	34.7	29.8	26.0	22.9	20.3	18.2	
		L/180	635.9	367.8	241.0	171.5	129.1	101.3	81.8	67.6	56.9	48.6	41.9	36.5	
		Pattern FP1	47.7	39.6	34.2	30.3	27.3	24.9	23.0	21.4	20.1	18.6	17.2	16.0	
		Pattern FP2	53.6	43.2	36.1	31.0									
		Pattern FP3	70.5	56.8	47.5	40.7	35.6	31.6	28.4	25.8	23.6	21.7	20.1	18.2	
	Pattern FP11	145.8	105.4	78.2	61.0	49.3	41.0	34.7	29.8	26.0	22.9	20.3	18.2		
	Three or More Spans	Bending and Shear	181.2	122.2	89.5	69.2	55.6	46.0	38.9	33.5	29.2	25.8	23.0	20.6	
		L/180	560.9	332.9	222.3	160.1	121.5	95.7	77.4	64.0	53.7	45.7	39.3	34.1	
		Pattern FP1	53.0	43.9	37.7	33.3	30.0	27.5	25.4	23.7	22.3	20.6	19.1	17.8	
		Pattern FP2	59.7	47.8	39.8	34.1									
Pattern FP3		78.4	62.8	52.4	44.9	39.3	34.9	31.4	28.5	26.1	24.1	22.4	20.6		
Pattern FP11	162.2	122.2	89.5	69.2	55.6	46.0	38.9	33.5	29.2	25.8	23.0	20.6			
5" CF-7.2 Insul Rib	Two Spans	Bending and Shear	161.4	112.5	84.7	66.9	54.7	45.8	39.1	33.9	29.7	26.3	23.5	21.2	
		L/180	683.8	405.9	272.4	198.1	152.1	121.4	99.7	83.6	71.3	61.6	53.8	47.4	
		Pattern FP1	48.1	40.0	34.6	30.6	27.6	25.2	23.3	21.7	20.4	18.7	17.4	16.2	
		Pattern FP2	54.1	43.6	36.5	31.4									
		Pattern FP3	71.1	57.3	48.0	41.2	36.1	32.0	28.8	26.1	23.9	22.0	20.3	18.9	
	Pattern FP11	147.0	112.5	84.7	66.9	54.7	45.8	39.1	33.9	29.7	26.3	23.5	21.2		
	Three or More Spans	Bending and Shear	188.0	128.6	95.3	74.6	60.6	50.6	43.1	37.3	32.8	29.1	26.0	23.5	
		L/180	614.4	374.4	256.0	188.4	145.8	116.9	96.2	80.7	68.7	59.3	51.6	45.3	
		Pattern FP1	53.2	44.0	37.9	33.5	30.1	27.6	25.5	23.8	22.4	20.6	19.1	17.9	
		Pattern FP2	59.8	47.9	40.0	34.3									
Pattern FP3		78.7	63.0	52.6	45.1	39.4	35.0	31.5	28.6	26.2	24.2	22.4	20.9		
Pattern FP11	162.6	128.6	95.3	74.6	60.6	50.6	43.1	37.3	32.8	29.1	26.0	23.5			
6" CF-7.2 Insul Rib	Two Spans	Bending and Shear	168.3	118.8	90.4	72.2	59.5	50.2	43.1	37.6	33.1	29.4	26.4	23.8	
		L/180	729.4	442.1	302.4	223.6	174.2	140.8	117.0	99.1	85.4	74.4	65.5	58.1	
		Pattern FP1	48.4	40.4	34.9	30.9	27.9	25.5	23.5	21.9	20.6	18.9	17.5	16.3	
		Pattern FP2	54.4	44.0	36.9	31.7									
		Pattern FP3	71.6	57.8	48.5	41.7	36.5	32.4	29.1	26.4	24.1	22.2	20.5	19.1	
	Pattern FP11	148.0	118.8	90.4	72.2	59.5	50.2	43.1	37.6	33.1	29.4	26.4	23.8		
	Three or More Spans	Bending and Shear	194.3	134.4	100.6	79.4	65.0	54.6	46.8	40.8	35.9	32.0	28.8	26.0	
		L/180	664.3	413.2	287.6	215.0	168.8	137.1	114.1	96.8	83.3	72.5	63.7	56.4	
		Pattern FP1	53.3	44.1	38.0	33.6	30.2	27.6	25.6	23.8	22.4	20.7	19.2	17.9	
		Pattern FP2	60.0	48.1	40.1	34.4									
Pattern FP3		78.9	63.2	52.7	45.2	39.5	35.1	31.6	28.7	26.3	24.2	22.5	21.0		
Pattern FP11	163.0	130.7	100.6	79.4	65.0	54.6	46.8	40.8	35.9	32.0	28.8	26.0			


Notes:

- The Load Span Table above is based on Allowable Stress Design (ASD). For loads calculated based on ASCE 7-10 (LRFD), please refer to section 2.4.1 of ASCE 7-10 for the applicable load combinations using Allowable Stress Design.
- Panel thickness includes rib height.
- Allowable positive or inward load is the lowest value of the panel bending and shear strength or deflection limit.
- Allowable suction or outward load is the lowest value of the panel bending and shear strength, deflection limit and connection strength for each fastener pattern. The numbers have been reduced to reflect the lowest value.
- Loads based on panel stress, deflection and connection design criteria are derived from ASTM E-72 testing.
- Allowable loads are calculated with a factor of safety of 2.5 for bending, 3.0 for shear and 2.0 for connection.
- Pattern FP1 is based on clip with (2) ¼"-14 Tek III's in minimum 16 ga. steel.
- Pattern FP2 is based on FP1 and (1) blind rivet in minimum 16 ga. steel.
- Pattern FP3 is based on FP1 and (2) blind rivets in minimum 16 ga. steel.
- Pattern FP11 is based on five (7.2" on center, low cell of product), ¼"-14 Tek III's with 5/8" neoprene bonded washer in minimum 12 ga. steel.
- The structural capacity of the girts are not considered and must be examined independently.







FP1 FASTENING PATTERN 1 SIDE JOINT FASTENING
REQUIRES TWO SELF-DRILLING OR SELF TAPPING SCREWS



FP2 (7.2) FASTENING PATTERN - FP3 (7.2) SIDE JOINT FASTENING
REQUIRES TWO SELF-DRILLING OR SELF TAPPING
SCREWS PLUS ONE BLIND RIVET



FP3 (7.2) FASTENING PATTERN - FP3 (7.2) SIDE JOINT FASTENING
REQUIRES TWO SELF-DRILLING OR SELF TAPPING
SCREWS PLUS TWO BLIND RIVETS



FP11 FASTENING PATTERN 11 WITH FIVE SELF TAPPING
SCREWS CENTER IN LOW CELLS WITH MIN. 20 GA.
NEOPRENE BONDED WASHER

(CONSULT METL-SPAN FOR FASTENER REQUIREMENTS NEEDED TO MEET SPECIFIC LOAD REQUIREMENTS)

**7.2 INSUL-RIB™
FASTENING PATTERNS**

**APPLICATION:
FASTENING**

FP 1, 2, 3 & 11

DATE: MAY 15, 2015