



CI-CFR-INDX1	SHEET INDEX (1 OF 2)
CI-CFR-INDX2	SHEET INDEX (2 OF 2)
CI-CFR-INFO	C & I DISCLAIMER
CI-CFR-LG	LEGEND
CI-CFR-JT-01	PANEL JOINT
CI-CFR-JT-02	PANEL JOINT SEQUENCE
CI-CFR-JT-03	PANEL JOINT LAYOUT
CI-CFR-SQ-01	PANEL INSTALLATION SEQUENCE (1 OF 3)
CI-CFR-SQ-02	PANEL INSTALLATION SEQUENCE (2 OF 3)
CI-CFR-SQ-03	PANEL INSTALLATION SEQUENCE (3 OF 3)
CI-CFR-AT-01	INTERMEDIATE ATTACHMENT
CI-CFR-EL-01	ENDLAP ATTACHMENT
CI-CFR-EL-01-A	ENDLAP ATTACHMENT
CI-CFR-EL-02	ENDLAP ATTACHMENT EXPLODED VIEW
CI-CFR-EL-03	ENDLAP STRUCTURAL SEALANT
CI-CFR-EL-04	ENDLAP LOWER PANEL
CI-CFR-EL-05	ENDLAP LOWER PANEL BUTYL TAPE SEALANT (1 OF 2)
CI-CFR-EL-06	ENDLAP LOWER PANEL BUTYL TAPE SEALANT (2 OF 2)
CI-CFR-EL-07	ENDLAP UPPER PANEL
CI-CFR-EL-08	ENDLAP CONDITIONS
CI-CFR-EV-01	LOW EAVE WITH TRIM
CI-CFR-EV-01-A	LOW EAVE WITH TRIM
CI-CFR-EV-G1	LOW EAVE WITH NORTHERN GUTTER
CI-CFR-EV-G1-A	LOW EAVE WITH NORTHERN GUTTER
CI-CFR-EV-G2	LOW EAVE NORTHERN GUTTER HANGAR
CI-CFR-EV-G3	LOW EAVE WITH STANDARD GUTTER
CI-CFR-EV-G3-A	LOW EAVE WITH STANDARD GUTTER
CI-CFR-EV-G4	LOW EAVE STANDARD GUTTER HANGAR
CI-CFR-EV-02	HIGH EAVE
CI-CFR-EV-02-A	HIGH EAVE
CI-CFR-RK-01	RAKE WITH HIGH PROFILE TRIM
CI-CFR-RK-01-A	RAKE WITH HIGH PROFILE TRIM
CI-CFR-RG-01	RIDGE
CI-CFR-RG-01-A	RIDGE
CI-CFR-RG-02	RIDGE EXPLODED VIEW
CI-CFR-RG-03	RIDGE CLOSURE ASSEMBLY (1 OF 2)
CI-CFR-RG-04	RIDGE CLOSURE ASSEMBLY (2 OF 2)
CI-CFR-RG-05	RIDGE FLASHING ASSEMBLY
CI-CFR-TR-01	TRANSITION WALL TO ROOF RAKE
CI-CFR-TR-01-A	TRANSITION WALL TO ROOF RAKE
CI-CFR-TR-02	TRANSITION STACK JOINT TO ROOF RAKE
CI-CFR-TR-02-A	TRANSITION STACK JOINT TO ROOF RAKE



CI-CFR-TR-03	TRANSITION CONTINUOUS WALL TO ROOK RAKE
CI-CFR-TR-03-A	TRANSITION CONTINUOUS WALL TO ROOF RAKE
CI-CFR-TR-04	TRANSITION WALL TO HIGH EAVE
CI-CFR-TR-04-A	TRANSITION WALL TO HIGH EAVE
CI-CFR-TR-05	TRANSITION STACK JOINT TO HIGH EAVE
CI-CFR-TR-05-A	TRANSITION STACK JOINT TO HIGH EAVE
CI-CFR-TR-06	TRANSITION CONTINUOUS WALL TO HIGH EAVE
CI-CFR-TR-06-A	TRANSITION CONTINUOUS WALL TO HIGH EAVE
CI-CFR-TR-07	TRANSITION MASONRY WALL TO HIGH EAVE
CI-CFR-TR-07-A	TRANSITION MASONRY WALL TO HIGH EAVE
CI-CFR-TR-08	TRANSITION MASONRY WALL TO RAKE
CI-CFR-TR-08-A	TRANSITION MASONRY WALL TO RAKE
CI-CFR-VL-01	VALLEY ASSEMBLY
CI-CFR-VL-02	VALLEY ROOF PLAN
CI-CFR-RC-01	ROOF CURB SECTIONS
CI-CFR-RC-02	ROOF CURB SUPPORT
CI-CFR-RC-03	ROOF CURB INSTALLATION (1 OF 5)
CI-CFR-RC-04	ROOF CURB INSTALLATION (2 OF 5)
CI-CFR-RC-05	ROOF CURB INSTALLATION (3 OF 5)
CI-CFR-RC-06	ROOF CURB INSTALLATION (4 OF 5)
CI-CFR-RC-07	ROOF CURB INSTALLATION (5 OF 5)
CI-CFR-RC-08	ROOF CURB INSTALLATION (1 OF 1)
CI-CFR-PB-01	PIPE BOOT (1 OF 2)
CI-CRR-PB-02	PIPE BOOT (2 OF 2)



## DISCLAIMER:

THESE DETAILS ARE PROVIDED AS A GUIDELINE FOR PROPER PANEL AND ASSOCIATED COMPONENT INSTALLATION, AND ARE BASED ON INDUSTRY ACCEPTED PRACTICES.

LOCATION OF VAPOR BARRIERS AND ASSOCIATED SEALANTS IN THESE DETAILS ARE BASED ON TYPICAL DESIGN PRACTICES FOR MOST U.S. CLIMATIC ZONES. (THE PRIMARY VAPOR BARRIER IS PLACED ON THE "WARM" SIDE IN WINTER).

PROJECTS LOCATED IN AREAS SUBJECT TO EXTREME WIND AND/OR HIGH SNOW LOADS MAY REQUIRE MODIFICATIONS TO THESE DETAILS – CONTACT METL–SPAN TECHNICAL SERVICES FOR SPECIFIC RECOMMENDATIONS.

WE RECOMMEND THE USE OF METL–SPAN SUPPLIED SEALANTS AND BUTYL TAPES FOR OPTIMUM PANEL SYSTEM PERFORMANCE.





## LEGEND:


LL LONG LIFE

BN BONDED NEOPRENE WASHER







- ① SET PANEL IN PLACE
- ② INSTALL CFR CLIP W/BUTYL TAPE SEALANT
- ③ SECURE TO PURLINS W/  
1/4" HEX HEAD FASTENERS




- ④ HAND "CRIMP" THE STANDING RIB/  
CLIP ASSEMBLY AT EACH CLIP LOCATION
- ⑤ INSTALL CONTINUOUS BUTYL TAPE SEALANT  
ON TOP OF MALE STANDING SEAM




- ⑥ TILT NEXT PANEL TO BE INSTALLED AT 45  
DEGREE ANGLE. ROTATE INTO POSITION.



- ⑦ USE CLAMPS TO ENSURE PROPER  
PANEL ENGAGEMENT
- ⑧ HAND CRIMP AT RIDGE, ENDLAP AND EAVES
- ⑨ INSTALL RIDGE, RAKE AND EAVE COMPONENTS  
THEN MECHANICALLY SEAM ROOF




1. ADD WALL PANEL THICKNESS (BOTH ENDS) PLUS OUT TO OUT DIMENSIONS OF RAKE STRUCTURAL SUPPORTS.
2. DIVIDE RESULT BY PANEL MODULE <sup>\*</sup>(30", 36" OR 42") TO DETERMINE NUMBER OF PANELS REQUIRED.
3. DIVIDE FRACTIONAL PANEL REMAINDER (IF ANY) BY 2 TO DETERMINE STARTING PANEL WIDTH. IF RESULT IS LESS THAN 12", THEN CUT STARTER PANEL TO REMOVE INTERIOR JOINT ONLY – LAST PANEL WILL NEED TO ACCOMMODATE THE REMAINDER (LAYOUT WILL BE ASYMMETRICAL ).





# APPLICABLE END TREATMENT



**CB#** COPED (CUT BACK) END (B END OF PANEL)

STANDARD CUT BACK IS 3" AT BOTTOM OF EVERY PANEL (2" AND 4" CUT BACK DIMENSIONS ARE AVAILABLE OPTIONS) IN CERTAIN CONDITIONS THE CB END MAY NOT BE REQUIRED DUE TO FIELD CUTTING OF PANEL OR OTHER FIELD CONDITIONS. IN THESE CASES, THE CUSTOMER WOULD NEED TO ORDER THE PANELS WITH AN "S" END.

**BP/NS** BACKER PLATE/ NOTCH & SWAGE (A END OF PANEL)


WHEN LAPPED, THE TOP OF THE BOTTOM PANEL IS TO BE NOTCHED 3" TO ALLOW FOR THE LAPPING OF THE PANEL ABOVE. A BACKER PLATE IS PLATE INSTALLED IN THE PANEL.

**S** SQUARE CUT (A OR B END PANEL)

PANELS ARE SQUARE (FLUSH) CUT. NO END TREATMENT REQUIRED


**BP** BACKER PLATE (A END OF PANEL)

NORMALLY ATTACHED AT THE TOP OF EVERY PANEL. IF PANELS ARE FIELD CUT, THIS PIECE CAN BE REMOVED AND THEN RE-INSERTED IN THE PANEL AFTER CUTTING. CAN ALSO BE ENTERED AS A "SHIP LOOSE" PIECES AND FIELD INSTALLED





## APPLICABLE END TREATMENT



**CB#** COPED (CUT BACK) END (B END OF PANEL)

STANDARD CUT BACK IS 3" AT BOTTOM OF EVERY PANEL (2" AND 4" CUT BACK DIMENSIONS ARE AVAILABLE OPTIONS) IN CERTAIN CONDITIONS THE CB END MAY NOT BE REQUIRED DUE TO FIELD CUTTING OF PANEL OR OTHER FIELD CONDITIONS. IN THESE CASES, THE CUSTOMER WOULD NEED TO ORDER THE PANELS WITH AN "S" END.

**BP/NS** BACKER PLATE/ NOTCH & SWAGE (A END OF PANEL)


WHEN LAPPED, THE TOP OF THE BOTTOM PANEL IS TO BE NOTCHED 3" TO ALLOW FOR THE LAPPING OF THE PANEL ABOVE. A BACKER PLATE IS PLATE INSTALLED IN THE PANEL.

**S** SQUARE CUT (A OR B END PANEL)

PANELS ARE SQUARE (FLUSH) CUT. NO END TREATMENT REQUIRED

**BP** BACKER PLATE (A END OF PANEL)

NORMALLY ATTACHED AT THE TOP OF EVERY PANEL. IF PANELS ARE FIELD CUT, THIS PIECE CAN BE REMOVED AND THEN RE-INSERTED IN THE PANEL AFTER CUTTING. CAN ALSO BE ENTERED AS A "SHIP LOOSE" PIECES AND FIELD INSTALLED



TWO PANEL LAYOUT WITH ENDLAPS

COMMERCIAL &  
INDUSTRIAL

PANEL INSTALLATION  
SEQUENCE

CI-CFR-SQ-02

DATE: Aug '19



# APPLICABLE END TREATMENT

**CB#** COPED (CUT BACK) END (B END OF PANEL)

STANDARD CUT BACK IS 3" AT BOTTOM OF EVERY PANEL (2" AND 4" CUT BACK DIMENSIONS ARE AVAILABLE OPTIONS) IN CERTAIN CONDITIONS THE CB END MAY NOT BE REQUIRED DUE TO FIELD CUTTING OF PANEL OR OTHER FIELD CONDITIONS. IN THESE CASES, THE CUSTOMER WOULD NEED TO ORDER THE PANELS WITH AN "S" END.

**BP/NS** BACKER PLATE/ NOTCH & SWAGE (A END OF PANEL)



WHEN LAPPED, THE TOP OF THE BOTTOM PANEL IS TO BE NOTCHED 3" TO ALLOW FOR THE LAPPING OF THE PANEL ABOVE. A BACKER PLATE IS PLATE INSTALLED IN THE PANEL.

**S** SQUARE CUT (A OR B END PANEL)

PANELS ARE SQUARE (FLUSH) CUT. NO END TREATMENT REQUIRED

**BP** BACKER PLATE (A END OF PANEL)

NORMALLY ATTACHED AT THE TOP OF EVERY PANEL. IF PANELS ARE FIELD CUT, THIS PIECE CAN BE REMOVED AND THEN RE-INSERTED IN THE PANEL AFTER CUTTING. CAN ALSO BE ENTERED AS A "SHIP LOOSE" PIECES AND FIELD INSTALLED




COMMERCIAL &  
INDUSTRIAL

PANEL INSTALLATION  
SEQUENCE

CI-CFR-SQ-03


DATE: Aug '19




FASTENER NOTE:

THE NUMBER OF FASTENERS PER CLIP ARE BASED ON THE FOLLOWING CRITERIA

- \* SELF DRILLING, SELF-TAPPING SCREWS
  - \* 3 /CLIP IF PURLIN IS LESS THAN 12 GAUGE.
  - \* 2 /CLIP IF PURLIN IS GREATER OR EQUAL TO 12 GA.
- \* TYPE B SELF-TAPPING SCREWS – 2 /CLIP








T	PANEL CLIP
2"	4102GNC
2.5"	4125GNC
3"	4103GNC
4"	4104GNC
5"	4105GNC
6"	4106GNC


COMMERCIAL &  
INDUSTRIAL

ENDLAP  
ATTACHMENT


CI-CFR-EL-01-A


DATE: Aug '19







ENDLAP SUPPORT STRUCTURAL SECTION













LEADING EDGE SECTION




TRAILING EDGE SECTION






SINGLE ROOF PANEL LAYOUT  
WITH NO ENDLAPS




TWO PANEL LAYOUT  
WITH ENDLAPS




THREE PANEL LAYOUT  
WITH ENDLAPS

(\*) ADD WALL PANEL THICKNESS TO PANEL LENGTH








T	PANEL CLIP	EAVE TRIM		
2"	4102GNC	F3415		
2.5"	4125GNC	F3415		
3"	4103GNC	F3415		
4"	4104GNC	F3416		
5"	4105GNC	F3416		
6"	4106GNC	F3417		

COMMERCIAL &  
INDUSTRIAL


LOW EAVE WITH TRIM

CI-CFR-EV-01-A

DATE: Aug '19



\* ADD ADDITIONAL GUTTER SUPPORTS AT MIDPOINT BETWEEN STANDING SEAMS (CFR-42 ONLY)




T	PANEL CLIP	EAVE TRIM		
2"	4102GNC	F3415		
2.5"	4125GNC	F3415		
3"	4103GNC	F3415		
4"	4104GNC	F3416		
5"	4105GNC	F3416		
6"	4106GNC	F3417		


COMMERCIAL &  
INDUSTRIAL


LOW EAVE  
WITH NORTHERN GUTTER

CI-CFR-EV-G1-A

DATE: Aug '19








T	PANEL CLIP	EAVE TRIM	STANDARD GUTTER	
2"	4102GNC	F3415	F3420	
2.5"	4125GNC	F3415	F3420	
3"	4103GNC	F3415	F3420	
4"	4104GNC	F3416	F3421	
5"	4105GNC	F3416	F3421	
6"	4106GNC	F3417	F3422	

COMMERCIAL &  
INDUSTRIAL


LOW EAVE  
WITH STANDARD GUTTER


CI-CFR-EV-G3-A

DATE: Aug '19










T	PANEL CLIP	HIGH EAVE TRIM	
2"	4102GNC	F3340	
2.5"	4125GNC	F3340	
3"	4103GNC	F3340	
4"	4104GNC	F3341	
5"	4105GNC	F3341	
6"	4106GNC	F3342	


COMMERCIAL &  
INDUSTRIAL

HIGH EAVE

CI-CFR-EV-02-A

DATE: Aug '19





T	THRU PANEL FASTENER
2"	1132P
2.5"	1132P
3"	1140P
4"	1148P
5"	1156P
6"	1164P


WALL PANEL THICKNESS	ROOF PANEL THICKNESS	RAKE TRIM
2", 2.5", 3"	2", 2.5", 3"	F3430
2", 2.5", 3"	4", 5"	F3431
2", 2.5", 3"	6"	F3432
4", 5"	2", 2.5", 3"	F3433
4", 5"	4", 5"	F3434
4", 5"	6"	F3435
6"	2", 2.5", 3"	F3330
6"	4", 5"	F3331
6"	6"	F3332


COMMERCIAL &  
INDUSTRIAL

RAKE WITH HIGH PROFILE TRIM

CI-CFR-RK-01-A

DATE: Aug '19






T	PANEL CLIP			
2"	4102GNC			
2.5"	4125GNC			
3"	4103GNC			
4"	4104GNC			
5"	4105GNC			
6"	4106GNC			

COMMERCIAL &  
INDUSTRIAL



RIDGE

CI-CFR-RG-01-A


DATE: Aug '19





\* NUMBERS REFER TO SEQUENCE OF INSTALLATION















T	THRU PANEL FASTENER
2"	1132P
2.5"	1132P
3"	1140P
4"	1148P
5"	1156P
6"	1164P


COMMERCIAL &  
INDUSTRIAL

TRANSITION  
WALL TO ROOF RAKE

CI-CFR-TR-01-A

DATE: Aug '19






T	THRU PANEL FASTENER
2"	1132P
2.5"	1132P
3"	1140P
4"	1148P
5"	1156P
6"	1164P


COMMERCIAL &  
INDUSTRIAL

TRANSITION  
STACK JOINT TO ROOF RAKE

CI-CFR-TR-02-A


DATE: Aug '19






T	THRU PANEL FASTENER
2"	1132P
2.5"	1132P
3"	1140P
4"	1148P
5"	1156P
6"	1164P








T	PANEL CLIP
2"	4102GNC
2.5"	4125GNC
3"	4103GNC
4"	4104GNC
5"	4105GNC
6"	4106GNC


COMMERCIAL &  
INDUSTRIAL

TRANSITION  
WALL TO HIGH EAVE

CI-CFR-TR-04-A

DATE: Aug '19






T	PANEL CLIP
2"	4102GNC
2.5"	4125GNC
3"	4103GNC
4"	4104GNC
5"	4105GNC
6"	4106GNC


COMMERCIAL &  
INDUSTRIAL

TRANSITION  
STACK JOINT TO HIGH EAVE

CI-CFR-TR-05-A

DATE: Aug '19






T	PANEL CLIP
2"	4102GNC
2.5"	4125GNC
3"	4103GNC
4"	4104GNC
5"	4105GNC
6"	4106GNC


COMMERCIAL &  
INDUSTRIAL

TRANSITION  
CONTINUOUS WALL TO HIGH  
EAVE

CI-CFR-TR-06-A

DATE: Aug '19





T	PANEL CLIP
2"	4102GNC
2.5"	4125GNC
3"	4103GNC
4"	4104GNC
5"	4105GNC
6"	4106GNC


COMMERCIAL &  
INDUSTRIAL


TRANSITION  
MASONRY WALL TO HIGH EAVE

CI-CFR-TR-07-A

DATE: Aug '19








T	THRU PANEL FASTENER
2"	1132P
2.5"	1132P
3"	1140P
4"	1148P
5"	1156P
6"	1164P

COMMERCIAL &  
INDUSTRIAL

TRANSITION  
MASONRY WALL TO RAKE

CI-CFR-TR-08-A


DATE: Aug '19






#### SEQUENCE OF INSTALLATION:

- ① STRUCTURAL VALLEY SUPPORT PLATE
- ② CEE SHAPED SECURED TO VALLEY PLATE
- ③ FILL VOID W/RIGID INSULATION
- ④ INSTALL VALLEY TRIM
- ⑤ APPLY SEALANT TAPE
- ⑥ FIELD CUT ROOF PANELS. REMOVE CUT BACK
- ⑦ FASTEN ASSEMBLY


NOTE: NOT FOR DORMER CONDITIONS –  
CONTACT METL-SPAN FOR MORE INFORMATION







### SUB-FRAMING SUPPORT



### ROOF CURB SUPPORT CHANNEL



FACTORY LOCATED CURBS WITH A SINGLE PANEL RUNNING EAVE TO RIDGE: PANELS ARE TO BE DETAILED WITH AN ENDLAP AT THE UPSLOPE CURB LOCATION ONLY.

FIELD LOCATED CURBS WITH A SINGLE PANEL RUNNING EAVE TO RIDGE: PANELS AT CURB LOCATION MUST BE A MINIMUM OF 3" LONGER TO PERMIT FIELD CUTTING AND NOTCHING / REMOVAL OF FOAM AT UPSLOPE SPLICE LOCATION OF CURB.


FACTORY LOCATED CURBS ON MULTIPLE PANELS RUNNING EAVE TO RIDGE: PANELS MUST BE DETAILED FOR AN ENDLAP AT THE UPSLOPE CURB LOCATION.

FIELD LOCATED CURBS ON MULTIPLE PANELS RUNNING EAVE TO RIDGE: PANELS UPSLOPE OF CURB LOCATION MUST BE A MINIMUM OF 3" LONGER TO PERMIT FIELD CUTTING AND NOTCHING / REMOVAL OF FOAM AT UPSLOPE SPLICE LOCATION OF CURB.

### ROOF ERECTION SEQUENCE IS LEFT TO RIGHT ON EACH PLANE

AP SUPPORT ANGLE UNDER CURB AREA ONLY.  
L 2 X 4 X 16GA FIELD CUT TO LENGTH.


LD FABRICATE AND FIELD LOCATE ENDLAP.  
REFERENCE STANDARD ENDLAP




STEP 1


ROOF CURBS MUST BE INSTALLED AS THE ROOF PANELS ARE INSTALLED


THESE DRAWINGS ARE FOR CONCEPTUAL PURPOSES ONLY.  
INDIVIDUAL DETAILS MAY VARY. REFERENCE SHOP DRAWINGS  
AND/OR DESIGN INSTALLATIONS MANUAL.






STEP 3





TAPE AND TUBE SEALANT  
AS RECOMMENDED BY  
BUILDING MANUFACTURER


1. ON FULLY SHEETED ROOF, SET CURB IN PLACE. CURB BASE FLANGE WILL GO TO NEAREST HIGH AT A SEAM (MINIMUM 6" CLEARANCE).
2. MARK BASE FLANGE LOCATIONS AND THROAT AREA. DO NOT USE LEAD PENCIL.
3. LOCATE AND MARK ROOF OPENING CUT LINE. ALLOW FOR 3" PANEL LAP ON UPSLOPE. ALLOW FOR 4" RIB CLOSURE DOWNSLOPE (LENGTH OF CURB MINUS 7").
4. IF C-CHANNEL SUPPORT IS REQUIRED, SEE DETAIL OF C-CHANNEL ASSEMBLY. POSITION UNDER VERTICAL PART OF CURB, EDGE OF SUB-FRAME, AND C-CHANNEL.
5. LAYOUT THROAT OPENING CUT LINE AND CUT THROUGH EXTERIOR PANEL, INSULATION AND INTERIOR PANEL AND ACCORDING TO BUILDING MANUFACTURER'S RECOMMENDATIONS.
6. LAYOUT ROOF PANEL CUT LINE AND CUT THROUGH EXTERIOR PANEL ONLY. REMOVE EXTERIOR PANEL LEAVING THE INSULATION FACE SHOWING.
7. REMOVE CUT PANELS FROM ROOF OPENING AND CLEAN UP ALL METAL SHAVINGS AND DEBRIS.
8. NO SCREWS REQUIRED IN THE C-CHANNEL. IT WILL BE SECURED WHEN CURB IS FASTENED DOWN.
9. APPLY A STRIP OF SEALANT TAPE ON UPPER SIDE OF UPHILL BASE FLANGE. ON DOWNHILL BASE FLANGE, APPLY SEALANT TAPE TO BOTTOM (UNDERNEATH) SIDE OF BASE FLANGE.
10. GENEROUSLY CAULK SEAM WHERE CURB BASE BUTTS TO ROOF PANEL.



DO RECOMMENDED SCREWS PER PANEL, UPHILL AND DOWNHILL IN CURB BASE FLANGE.  
 CLEAN UP INSTALLATION DEBRIS BEFORE LEAVING AREA.

## NOTE:

FOR ROOF PITCHES GREATER THAN 4:12  
CONSIDER USING NEXT LARGER SIZE BOOT.  
(DO NOT INSTALL OVER PANEL RIBS)



## STEPS FOR INSTALLING PIPE BOOT FLASHING:

- 1.) CUT PIPE BOOT TO PIPE DIAMETER MARKED ON THE CONE (INCHES AND MILLIMETERS). ALLOW 1/2" [13] STRAIGHT COLLAR AGAINST THE PIPE FOR MAXIMUM SEALING.
- 2.) CLEAN AREA FLASHING IS TO BE INSTALLED AGAINST THE PANEL THOROUGHLY.
- 3.) SLIDE BOOT OVER PIPE TO BE FLASHED.
- 4.) APPLY A 3/8" [10] Ø BEAD OF POLYURETHANE TO THE UNDER SIDE OF THE RIBBED ALUMINUM BASE.
- 5.) PRESS FLASHING TO CONTOURS OF ROOF PANEL. A BLUNT TOOL MAY BE USED TO PRESS BOOT INTO PLACE IN SHARPLY ANGLED AREAS.
- 6.) FASTEN FLASHING AS DESCRIBED IN DETAIL. WHILE FASTENING INSPECT BASE FOR GAPS BETWEEN THE PIPE BOOT BASE AND ROOF PANEL. TOOL EXCESS POLYURETHANE SEALANT INTO THE EDGE OF THE BOOT BASE.

