Health Product Declaration v2.2

created via: HPDC Online Builder

HPD UNIQUE IDENTIFIER: 26250

CLASSIFICATION: 07 42 13.19 Insulated Metal Wall Panels

PRODUCT DESCRIPTION: ThermalSafe insulated metal panels have a 3"-to 8"-thick non-combustible mineral wool core and fire resistant ratings of one-to three-hours depending on thickness and a 90 minute rating for ceiling. The ouside protective barrier uses 24 or 26 gauge hot dipped galvanized steel. Insulated metal panels sold under the Metl-Span brand. ThermalSafe product lines include TS42, TS42 NC, TS42 NEF.

Section 1: Summary

Nested Method / Material Threshold

CONTENT INVENTORY

Inventory Reporting Format

- Nested Materials Method
- C Basic Method

Threshold Disclosed Per

- Material
- Product

Threshold Level

- C 100 ppm
- C 1,000 ppm O Per GHS SDS

Other

Residuals/Impurities

- C Considered
- Not Considered

Explanation(s) provided for Residuals/Impurities?

Yes ○ No

All Substances Above the Threshold Indicated Are:

Characterized

% weight and role provided for all substances.

Screened

○ Yes Ex/SC ⊙ Yes ○ No

All substances screened using Priority Hazard Lists with

results disclosed.

Identified

○ Yes Ex/SC ⊙ Yes ○ No

All substances disclosed by Name (Specific or Generic)

and Identifier.

CONTENT IN DESCENDING ORDER OF QUANTITY

Summary of product contents and results from screening individual chemical substances against HPD Priority Hazard Lists and the GreenScreen for Safer Chemicals®. The HPD does not assess whether using or handling this product will expose individuals to its chemical substances or any health risk. Refer to Section 2 for further details.

MATERIAL | SUBSTANCE | RESIDUAL OR IMPURITY

GREENSCREEN SCORE | HAZARD TYPE

GLASS/MINERAL FIVER [GLASS / MINERAL FIBER (POST-

CONSUMER RECYCLED) (GLASS / MINERAL FIBER (POST-

CONSUMER RECYCLED)) LT-UNK] STEEL [STEEL (STEEL) NoGS]

POLYURETHANE [POLYURETHANE (POLYURETHANE) LT-P1] ZINC

[ZINC (ZINC) LT-P1 | END | MUL | AQU | PHY] TITANIUM DIOXIDE [

TITANIUM DIOXIDE (TITANIUM DIOXIDE) LT-1 | CAN | END]

POLYVINYLIDENE FLUORIDE (1, 1-DIFLUROROETHENE) [

POLYVINYLIDENE FLUORIDE (1,1-DIFLUOROETHENE

HOMOPOLYMER) (POLYVINYLIDENE FLUORIDE (1,1-DIFLUOROETHENE HOMOPOLYMER)) LT-UNK] POLYESTER [

POLYESTER (POLYESTER) NoGS]

Number of Greenscreen BM-4/BM3 contents ... 0

Contents highest concern GreenScreen

Benchmark or List translator Score ... LT-1

Nanomaterial ... No

INVENTORY AND SCREENING NOTES:

VOLATILE ORGANIC COMPOUND (VOC) CONTENT

VOC Content data is not applicable for this product category.

CERTIFICATIONS AND COMPLIANCE See Section 3 for additional

VOC emissions: VOC Emissions

LCA: Environmental Product Declaration (EPD)

CONSISTENCY WITH OTHER PROGRAMS

No pre-checks completed or disclosed.

Third Party Verified?

O Yes

No

PREPARER: Self-Prepared

VERIFIER:

VERIFICATION #:

SCREENING DATE: 2021-10-18 PUBLISHED DATE: 2021-10-18 EXPIRY DATE: 2024-10-18

Section 2: Content in Descending Order of Quantity

This section lists contents in a product based on specific threshold(s) and reports detailed health information including hazards. This HPD uses the inventory method indicated above, which is one of three possible methods:

- Basic Inventory method with Product-level threshold.
- Nested Material Inventory method with Product-level threshold
- · Nested Material Inventory method with individual Material-level thresholds

Definitions and requirements for the three inventory methods and requirements for each data field can be found in the HPD Open Standard version 2.2, available on the HPDC website at: www.hpd-collaborative.org/hpd-2-2-standard

GLASS/MINERAL FIVER %: 48.0000 - 78.0000

MATERIAL THRESHOLD: Per OSHA MSDS

RESIDUALS AND IMPURITIES CONSIDERED: No MATERIAL TYPE: Geologically Derived Material

RESIDUALS AND IMPURITIES NOTES: There are no know residuals or impurities and there is no mention of them in their MSDS.

OTHER MATERIAL NOTES: The variability in mineral wool content is due to the variation in panel core thickness (anywhere from 3- to 8-inches). Thickness is determined by application needs

GLASS / MINERAL FIBER (POST-CONSUMER RECYCLED) (GLASS / MINERAL FIBER (POST-CONSUMER RECYCLED))

ID: 65997-17-3

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-10-18 20:08:41

%: 48.0000 - 78.0000 GS: LT-UNK RC: PostC NANO: No SUBSTANCE ROLE: Insulator

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

STEEL %: 21.0000 - 49.0000

MATERIAL THRESHOLD: Per OSHA MSDS

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Metal

RESIDUALS AND IMPURITIES NOTES: There are no known residuals or impurities and there are none listed on their MSDS.

OTHER MATERIAL NOTES: Galvalume or Galvanized (Hot Dipped) Sheet steel is used.

Steel includes alloying metals with the following CAS numbers: 1309-37-1, 1314-13-2, 1314-62-1, 7439-96-5, 7440-47-3, 7440-21-3, 7440-02-0, 7440-62-2. The amount of steel used per panel unit area is the same; however the relative amount varies due to variation in mineral wool core thickness (anywhere from 3- to8-inches).

STEEL (STEEL) ID: 12597-69-2

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-10-18 20:08:41

%: 57.5000 - 82.5000 GS: NoGS RC: Both NANO: No SUBSTANCE ROLE: Alloy element

HAZARD TYPE AGENCY AND LIST TITLES WARNINGS

None found No warnings found on HPD Priority Hazard Lists

SUBSTANCE NOTES:

POLYURETHANE %: 0.9000 - 1.5000

MATERIAL THRESHOLD: Per OSHA MSDS

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: There are no known residuals or impurities and none mentioned in their MSDS.

OTHER MATERIAL NOTES: Purchased adhesive however the relative amount varies due to variation in mineral wool core thickness.

HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-10-18 20:08:42 %: 0.9000 - 1.5000 GS: LT-P1 RC: None NANO: No SUBSTANCE ROLE: Adhesive HAZARD TYPE AGENCY AND LIST TITLES WARNINGS None found No warnings found on HPD Priority Hazard Lists

ZINC %: 0.1000 - 0.3000

MATERIAL THRESHOLD: Per OSHA MSDS

SUBSTANCE NOTES:

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Metal

RESIDUALS AND IMPURITIES NOTES: There is no known residuals or impurities and none mentioned in their MSDS.

OTHER MATERIAL NOTES: Zinc is associated with three primary hazards: aquatic toxicity, flammability, and respiratory. The last is applicable only to inhaled forms, which does not include galvanized coil. The risk of aquatic toxicity will depend on whether the zinc in the galvanized layer will leach from the panel into the environment. Finally, the risk of flammability is low as the product is designed to be fire resistant.

| HAZARD SCREENING METHOD | Pharos Chemical and Materials Library | HAZA | ARD SC | REENING DAT | E: 2021-10-1 | 8 20:08:42 |
|-------------------------|---|--|--|-----------------|--------------|---------------------|
| %: 0.1000 - 0.3000 | GS: LT-P1 | RC: N | None | NANO: No | SUBSTANC | E ROLE: Galvanizing |
| HAZARD TYPE | AGENCY AND LIST TITLES | | WARI | NINGS | | |
| END | TEDX - Potential Endocrine Disruptors | rs Potential Endocrine Disruptor | | | | |
| MUL | German FEA - Substances Hazardous to Waters | | Class 2 - Hazard to Waters | | | |
| AQU | EU - GHS (H-Statements) | H400 - Very toxic to aquatic life [Hazardous aquatic environment (acute) - Category 1] | | | | |
| AQU | EU - GHS (H-Statements) | | H410 - Very toxic to aquatic life with long lasting effects [Hazardous to the aquatic environment (chronic) - Category 1] | | | |
| РНҮ | EU - GHS (H-Statements) | | H250 - Catches fire spontaneously if exposed to air [Pyrophoric liquids; Pyrophoric solids - Category 1] | | | |
| РНҮ | EU - GHS (H-Statements) | | H260 - In contact with water releases flammable gases which may ignite spontaneously [Substances and mixtures which, in contact with water, emit flammable gases - Category 1] | | | |

TITANIUM DIOXIDE %: 0.0200 - 0.0700

MATERIAL THRESHOLD: Per OSHA MSDS

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Other: Coil pre-coat component (pigment)

RESIDUALS AND IMPURITIES NOTES: There is no known residuals or impurities and there are none mentioned in their MSDS.

OTHER MATERIAL NOTES: The primary hazard associated with titanium dioxide is cancer. Despite this fact, titanium dioxide is often used in cosmetic and skin care products, including the majority of sunscreens. In the product, it is used as a pigment and embedded in the polyurethane-based coil coating.

TITANIUM DIOXIDE (TITANIUM DIOXIDE) ID: 13463-67-7 HAZARD SCREENING METHOD: Pharos Chemical and Materials Library HAZARD SCREENING DATE: 2021-10-18 20:08:43 %: 0.0200 - 0.0700 GS: LT-1 RC: None NANO: No SUBSTANCE ROLE: Pigment **HAZARD TYPE** AGENCY AND LIST TITLES **WARNINGS** CAN **US CDC - Occupational Carcinogens** Occupational Carcinogen CAN CA EPA - Prop 65 Carcinogen - specific to chemical form or exposure route CAN **IARC** Group 2B - Possibly carcinogenic to humans - inhaled from occupational sources CAN MAK Carcinogen Group 3A - Evidence of carcinogenic effects but not sufficient to establish MAK/BAT value

SUBSTANCE NOTES:

END

CAN

CAN

POLYVINYLIDENE FLUORIDE (1, 1-DIFLUROROETHENE)

%: 0.0000 - 0.0800

MATERIAL THRESHOLD: Per OSHA MSDS

RESIDUALS AND IMPURITIES CONSIDERED:

No

TEDX - Potential Endocrine Disruptors

EU - GHS (H-Statements)

MATERIAL TYPE: Polymeric

Material

Carcinogen Group 4 - Non-genotoxic carcinogen with

H351 - Suspected of causing cancer [Carcinogenicity -

Potential Endocrine Disruptor

low risk under MAK/BAT levels

Category 2]

RESIDUALS AND IMPURITIES NOTES: There are no known residuals or impurities and there are none mentioned on their MSDS.

OTHER MATERIAL NOTES: Binder used as a coil pre-coat component

POLYVINYLIDENE FLUORIDE (1,1-DIFLUOROETHENE HOMOPOLYMER) (POLYVINYLIDENE FLUORIDE (1,1-DIFLUOROETHENE HOMOPOLYMER))

MAK

ID: 24937-79-9

| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | HAZARD SCREENING DATE: | | 2021-10-18 20:08:43 | |
|--------------------------|---------------------------------------|------------------------|----------------|-----------------------------------|--|
| %: 0.0000 - 0.0800 | GS: LT-UNK | RC: None | NANO: No | SUBSTANCE ROLE: Coating | |
| HAZARD TYPE | AGENCY AND LIST TITLES | WARNINGS | | | |
| None found | | | No warnings fo | ound on HPD Priority Hazard Lists | |
| | | | | | |

SUBSTANCE NOTES:

POLYESTER %: 0.0000 - 0.0600

MATERIAL THRESHOLD: Per OSHA MSDS

RESIDUALS AND IMPURITIES CONSIDERED: No

MATERIAL TYPE: Polymeric Material

RESIDUALS AND IMPURITIES NOTES: There are no known residuals or impurities and there are none mentioned on their MSDS.

OTHER MATERIAL NOTES: Binder used as a coil pre-coat component.

| POLYESTER (POLYESTER) ID: 113669-95-7 | | | | | |
|--|---------------------------------------|---|-----------------|-------------------------|--|
| HAZARD SCREENING METHOD: | Pharos Chemical and Materials Library | Chemical and Materials Library HAZARD SCREE | | 2021-10-18 20:08:44 | |
| %: 0.0000 - 0.0600 | GS: NoGS | RC: None | NANO: No | SUBSTANCE ROLE: Coating | |
| HAZARD TYPE | AGENCY AND LIST TITLES | WARNINGS | | | |
| None found | | No warnings found on HPD Priority Hazard | | | |

SUBSTANCE NOTES:



Section 3: Certifications and Compliance

This section lists applicable certification and standards compliance information for VOC emissions and VOC content. Other types of health or environmental performance testing or certifications completed for the product may be provided.

| $\mathbf{V} \cap \mathbf{C}$ | ~ ENA | | |
|------------------------------|--------|------|-----|
| VU | - EIVI | แออเ | ONS |

VOC Emissions

CERTIFYING PARTY: Self-declared APPLICABLE FACILITIES: AII

ISSUE DATE: 2021-10- EXPIRY DATE:

CERTIFIER OR LAB: N/A

18

CERTIFICATE URL:

CERTIFICATION AND COMPLIANCE NOTES: Neither panels nor sealant have been tested in accordance with CDPH Standard Method for VOC emissions or similar test.

LCA

Environmental Product Declaration (EPD)

CERTIFYING PARTY: Third Party APPLICABLE FACILITIES: All

01

ISSUE DATE: 2019-07- EXPIRY DATE: 2024-

CERTIFIER OR LAB: UL

07-01 **Environment**

CERTIFICATE URL: https://spot.ul.com/mainapp/products/detail/5cba1d8f55b0e889748932be?

page_type=Products%20Catalog

CERTIFICATION AND COMPLIANCE NOTES:

Section 4: Accessories

This section lists related products or materials that the manufacturer requires or recommends for installation (such as adhesives or fasteners), maintenance, cleaning, or operations. For information relating to the contents of these related products, refer to their applicable Health Product Declarations, if available.

No accessories are required for this product.

Section 5: General Notes

ThermalSafe insulated metal panels have a 3"-to 8"-thick non-combustible mineral wool core and fire resistant ratings of one-to three-hours depending on thickness and a 90 minute rating for ceiling. The ouside protective barrier uses 24 or 26 gauge hot dipped galvanized steel.

Insulated metal panels sold under the Metl-Span brand. ThermalSafe product lines include TS42, TS42 NC, TS42 NEF.

MANUFACTURER INFORMATION

MANUFACTURER: Metl-Span
ADDRESS: 1720 Lakepointe Drive

Suite 101

Lewisville Texas 75057, USA WEBSITE: www.metlspan.com

CONTACT NAME: Amanda Storer TITLE: Marketing Brand Manager

PHONE: 972.221.6656

EMAIL: ajstorer@metlspan.com

The listed contact is responsible for the validity of this HPD and attests that it is accurate and complete to the best of his or her knowledge.

KEY

Hazard Types

AQU Aquatic toxicity

CAN Cancer

DEV Developmental toxicity
END Endocrine activity
EYE Eye irritation/corrosivity

GEN Gene mutation

GLO Global warming

LAN Land toxicity

MAM Mammalian/systemic/organ toxicity

MUL Multiple
NEU Neurotoxicity

NF Not found on Priority Hazard Lists

OZO Ozone depletion

PBT Persistent, bioaccumulative, and toxic

PHY Physical hazard (flammable or reactive)

REP Reproductive

RES Respiratory sensitization

SKI Skin sensitization/irritation/corrosivity

UNK Unknown

GreenScreen (GS)

BM-4 Benchmark 4 (prefer-safer chemical)

BM-3 Benchmark 3 (use but still opportunity for improvement)

BM-2 Benchmark 2 (use but search for safer substitutes)

BM-1 Benchmark 1 (avoid - chemical of high concern)

BM-U Benchmark Unspecified (due to insufficient data)

LT-P1 List Translator Possible 1 (Possible Benchmark-1)

LT-1 List Translator 1 (Likely Benchmark-1)

LT-UNK List Translator Benchmark Unknown (the chemical is present on at least one GreenScreen Specified List, but the information contained within the list did not result in a clear mapping to a LT-1 or LTP1 score.)

NoGS No GreenScreen.

Recycled Types

PreC Pre-consumer recycled content

PostC Post-consumer recycled content

UNK Inclusion of recycled content is unknown

None Does not include recycled content

Other Terms:

GHS SDS Globally Harmonized System of Classification and Labeling of Chemicals Safety Data Sheet

Inventory Methods:

Nested Method / Material Threshold Substances listed within each material per threshold indicated per material Nested Method / Product Threshold Substances listed within each material per threshold indicated per product

Basic Method / Product Threshold Substances listed individually per threshold indicated per product

Nano Composed of nano scale particles or nanotechnology

Third Party Verified Verification by independent certifier approved by HPDC

Preparer Third party preparer, if not self-prepared by manufacturer

Applicable facilities Manufacturing sites to which testing applies

The Health Product Declaration (HPD) Open Standard provides for the disclosure of product contents and potential associated human and environmental health hazards. Hazard associations are based on the HPD Priority Hazard Lists, the GreenScreen List Translator™, and when available, full GreenScreen® assessments. The HPD Open Standard v2.1 is not:

- a method for the assessment of exposure or risk associated with product handling or use,
- a method for assessing potential health impacts of: (i) substances used or created during the manufacturing process or (ii) substances created after the product is delivered for end use.

Information about life cycle, exposure and/or risk assessments performed on the product may be reported by the manufacturer in appropriate Notes sections, and/or, where applicable, in the Certifications section.

The HPD Open Standard was created and is supported by the Health Product Declaration Collaborative (the HPD Collaborative), a customer-led organization composed of stakeholders throughout the building industry that is committed to the continuous improvement of building products through transparency, openness, and innovation throughout the product supply chain.

The product manufacturer and any applicable independent verifier are solely responsible for the accuracy of statements and claims made in this HPD and for compliance with the HPD standard noted.